

EN

**UNDERBODY ARMOUR INSTALLATION MANUAL
(RADIATOR / ENGINE BAY, GEARBOX, TRANSFER CASE)**

DE

**MONTAGEEINLEITUNG FÜR UNTERBODENSCHUTZSYSTEM
(RADIATOR-, MOTOR-, GETRIEBE-, DIFFERENZIALSCHUTZ)**



Underbody Armour for:

Toyota Hilux (2007-2015)

2333.5790.1;	2333.5791.1;	2333.5792.1;
2333.5790.1/6;	2333.5791.1/6;	2333.5792.1/6;
2111.5790.1/3;	2111.5791.1/3;	2111.5792.1/3;





**LOCATION/POSITION
ARROW ANORDNUNG/
POSITION**




**MOVEMENT ARROW
BEWEGUNGSRICHTUNG**




**SCREW ARROW
DREHRICHTUNG**







EN Regular fasteners
DE Originale montageile




EN Regular fasteners
DE Originale montageile




EN Screw a several turns
DE Für wenigen Umdrehungen befestigen




EN Loosen bolts
DE Bolzen lockern




EN Drill
DE Bohrer




EN Screwdriver
DE Schraubenzieher



EN Office Knife
DE Büromesser


A

1x

B


M8x30

4x

C


M10x30

14x

D


Ø 8

4x


E

Ø 10


18x

F


1x

G

1x


H

1x

I


M10x65/15

2x

J


M10x100/50



2x



K



M10



2x




































(EN) Mounting requirements:

Underbody Armour is developed individual for each car model.

Underbody Armour must be mounted according to installation manual by an authorized car dealer or by a special car repair stations.

Underbody Armour is to be installed to original points and holes of the power units of the car.

Installed properly Underbody Armour doesn't scrape another parts and assembly of the car.

(DE) Montageanleitung:

Der Unterfahr-/Unterbodenschutz wurde für jedes Fahrzeug individuell entwickelt. Der Unterfahr-/Unterbodenschutz ist gemäß Installationsanleitung des Herstellers bei einer autorisierten Werkstatt oder Autohändler zu montieren. Der Unterbodenschutz wird an den originalen Befestigungsbohrungen der Karosserie montiert. Bei Montage gemäß Herstellervorgaben werden keine anderen Karosserieteile beschädigt oder in Mitleidenschaft gezogen.

(EN) Working requirements:

Underbody Armour is designed for use and drive of the vehicle in conditions considere by the car manufacture.

While driving the carat speed, cases of collisions with large obstacles and objects need to be excluded.

In the case of a collision with an obstacle Underbody Armour and the vehicle must be inspected in a specialized car repair stations for damage of the components and assemblies and suitability for further use.

(DE) Herstellervorgaben:

Der Unterfahr-/Unterbodenschutz ist gemäß den Vorgaben des Fahrzeugherstellers zu verwenden. Das Befahren und Zusammenstoßen von/mit Hindernissen und großen Objekten ist zu unterlassen. Nach erfolgtem Zusammenstoß muss die Funktionsfähigkeit des Fahrzeuges und/oder entstandene Mängel von einer autorisierten Werkstatt überprüft werden.

(EN) Warranty:

Warranty period - 12 months.

(DE) Gewähr:

Die Dauer der Gewährleistung beträgt 12 Monate.

(EN) Warranty terms and conditions:

Underbody Armour is installed on the car, with good condition of the body and the assembly parts (the car, that was not involved in the accident).

Absence of mechanical damages of the Underbody Armour caused by a head-on crush;

Compliance with all installation requirements;

Absence of powder coating damages of the Underbody Armour;

The manufacturer is not liable for any damage caused to the vehicle, the life and health of people in the event of breach of the installation and using of Underbody Armour. The manufacturer has the right to change the design of Underbody Armour.

(DE) Gewährleistung:

Der Unterfahr-/Unterbodenschutz muss ohne Beschädigung und/oder Änderungen an Karosserie montiert worden sein. Es dürfen keine Schäden durch die Kollision mit Hindernissen/Gegenständen entstanden sein. Die Vorgaben der Montageanleitung müssen exakt eingehalten werden. Es dürfen keine Schäden/Kratzspuren an der Pulverbeschichtung vorhanden sein. Der Hersteller übernimmt keine Haftung für Fahrzeugschäden jedweder Art und gesundheitliche Gefährdungen durch fehlerhafte Montage und Nutzung des Unterbodenschutzes. Der Hersteller behält sich vor, Design und Konstruktionsänderungen des Unterbodenschutzes zu ändern.

All products are certified
Alle Produkte sind zertifiziert



TOYOTA HILUX

No.: 5793.1/6 Fuel tank


Year: 2005-2015

Engine: 2.5TD; 2.7i; 3.0TD

Transmission: All

FITTING KIT

1. Bolt M8x20.....	1 pc
2. Bolt M10x25.....	6 pc
3. Bolt M10x1.25x25.....	1 pc
4. Insert nut M8.....	1 pc
5. Insert nut M10x65/32.5.....	2 pc
6. Washer 8.....	1 pc
7. Washer 10.....	7 pc
8. Bracket 1.....	1 pc
9. Bracket 2.....	1 pc
10. Bracket 3.....	1 pc



INSTALLATION INSTRUCTIONS

1. Remove factory plastic guard.
2. Place insert nut above aperture in underframe near fuel tank, then screw bolt M10x25 into it.
3. Place bracket 1 on mounted bolt M10x25, fix it to underframe with insert nut M8 and bolt M8x20..
4. Place insert nut M10x65/32.5 above aperture in underframe near rear left mount of fuel tank, then screw bolt M10x25 into it.
Place bracket 2 on mounted bolt M10x25.
5. Fix bracket 3 into original threaded aperture near fuel tank with bolt M10x1.25x25..
6. Fix skid plate to mounted brackets with bolts M10x25.
7. Tighten all screws (50 Nm for M10, 30 Nm for M8, 10 Nm for M6). Do not use pneumatic or power tools to tighten.